

Great value, easily personalized

The TP3 series is a unique, highly customizable portable radio. Available in DMR Tier 2 and analog, it puts the power to choose the color, display, keypad, and labels for each radio in your hands.

If your needs evolve, the TP3 allows you to change these options quickly and cost-effectively - any time!

The TP3 is the only radio that gives you the power to choose - and the power to change - with such ease and affordability.





FEATURES AND BENEFITS

The TP3 series is a great value, dual mode portable radio, capable of Analog Conventional and DMR Tier 2. Each radio is highly customizable and can be fit with the color, keypad, and label of your choice.

Smart features in the TP3350 also include voice annunciation, GPS, Man Down, Bluetooth, and vibration alert.

Choose Your Own Color

Each TP3 radio is available in a range of colors, giving your organization the freedom to choose radios that look the way you want. Organize your portables using color to quickly identify specific teams. Colors can be selected to match your brand guidelines, or to stand out better in environments they need to be seen in.

The front panel of the radio is interchangeable, allowing you to purchase a black radio, then later change it to a different color - saving time and money over purchasing a whole new portable.

Choose Your Display and Keypad

Three keypad options are available:

- No Key, No Display model (0-key)
- 4-Key, Color Display model (4-key)
- 16-Key, Color Display (16-key)

The 4-Key and 16-key models come with a 160x128 pixel, 1.77" color display. You can customize the power-up display to contain your

logo, radio ID, assigned owner, or any other image. The display can be used to select from the 2000 channels, for text messages, caller ID, or identifying talk groups.

The 0-Key radio does not come with a display. Should you want to upgrade to a 4-key or 16-key radio with a display, the cover can quickly and easily be changed, instantly enhancing your portable to include the display and keys.

Choose Your Label

Each radio is built with designated spaces for custom labels. Die-cut labels are high-tack adhesives, color-customized, and waterproof, alcohol, chemical and smudge resistant.

Custom-designed labels can be personalized to carry your brand logo, specific talk groups or radio type, user identification, or anything else you can imagine. This means that your radio can be completely unique to your organization, and individual radios can be personalized for each user.

Voice Annunciation

Keep your eyes up and focused on the task at hand while changing channels or features with the voice annunciation capabilities. The loud and clear voice will give users confidence their radio is set up and functioning correctly.

Increase Health and Safety

Reliable and clear communications are essential for health and safety. If someone on your team needs assistance, you need to trust that they can call for help. Each TP3 radio is remarkably simple to use, meaning users can quickly and easily connect to the right person or group.

If safety is a high priority in your industry, then the TP3350 model provides a series of features that help increase worker safety, such as:

- **Vibration alerts** to help ensure every text message is detected.
- **GPS**, which allows you to locate your staff, check their progress, and ensure they aren't lost or off track.
- **Man Down**, which sends an alert to dispatch when the radio detects unusual tilt or inactivity, such as when someone on your team has been injured and collapses.

Combined, GPS and Man Down enable you to quickly identify the injured person's location and the location of other workers nearby. This means help can arrive within a matter of minutes, even seconds. Fast response time can mean the difference between life and death.

GENERAL	136-174MHZ*	400-480 / 450-520MHZ*
Frequency stability	1.0 ppm -22°F to 140°F , 77°F ref (-30 to +60°C, 25°C ref)	1.0 ppm -22°F to 140°F , 77°F ref (-30 to +60°C, 25°C ref)
Digital Protocol	ETSI TS 102 361-1, 2, 3	ETSI TS 102 361-1, 2, 3
Battery voltage	7.5V	7.5V
Standard battery capacity	2000mAH Lithium-ion	2000mAH Lithium-ion
Channel capacity 0-Key radio	32	32
Channel capacity 4-key and 16-key radios	2000	2000
RECEIVER	136-174MHZ*	400-480 / 450-520MHZ*
Sensitivity analog	0.22μV (-120dBm) @ 12dB SINAD	0.22μV (-120dBm) @ 12dB SINAD
Sensitivity digital 5% BER	0.22μV (-120dBm) @ BER 5%	0.22μV (-120dBm) @ BER 5%
Intermodulation	TIA603 70dB; ETSI 65dB	TIA603 70dB; ETSI 65dB
Adjacent Channel Selectivity	TIA603 70dB; ETSI 65dB@25kHz TIA603 60dB; ETSI 60dB@12.5kHz	TIA603 70dB; ETSI 65dB@25kHz TIA603 60dB; ETSI 60dB@12.5kHz
Spurious Rejection TIA603	TIA603 75dB; ETSI 70dB	TIA603 75dB; ETSI 70dB
Conducted Spurious Emissions TIA603D, ETS300 086	-57dBm <1GHz, -47dBm >1GHz	-57dBm <1GHz, -47dBm >1GHz
Blocking	84dB	84dB
Rated Audio	750mW	750mW
Maximum Audio	1000mW	1000mW
Audio distortion	2% @ 500mW	2% @ 500mW
Audio response (300-3000Hz)	+1 to -3dB	-1 to -3dB
Receiver hum and noise	-40dB@12.5kHz	-40dB@12.5kHz
TRANSMITTER	136-174MHZ*	400-480 / 450-520MHZ*
Power output - Full Power	5W	4W
Power output - Low Power	1W	1W
Adjacent Channel Power	-60dB@12.5kHz -70dB@25kHz	-60dB@12.5kHz -70dB@25kHz
Conducted/Radiated Emissions	-36dBm <1GHz -30dBm >1GHz	-36dBm <1GHz -30dBm >1GHz
ENVIRONMENTAL	136-174MHZ*	400-480 / 450-520MHZ*
IP rating, Water Ingress	IP67	IP67
MIL810G	PROCEDURE	METHOD
Humidity	507.6	1
Vibration	514.6	1
Shock	516.6	1, 4

*Future release

